



CENTRAL CALIFORNIA
POWER



Product Quotation

**Prepared For:
DERRICK SPEIGHTS**

**CITY OF HOLLISTER
HOLLISTER CALIFORNIA**



**Prepared By:
Raul Portugal
CENTRAL CALIFORNIA POWER JCB
SHAFTER CA 93263
mobile:**

Image is for indicative purpose only and may not represent exact equipment being quoted



CENTRAL CALIFORNIA
POWER



Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

| | |
|--------------|--|
| GENERAL | One piece unitized mainframe with sway control, componentized driveline, and automatic rear axle stabilization system. |
| ENGINE | JCB Ecomax Turbo charged 4.4 L (269 cu in) 109 HP Tier 4 Final, Dual element air cleaner, spin-on fuel filter, fuel/water separator, spin on vertical oil filter, anti-freeze protection to -30 deg. F. |
| TRANSMISSION | JCB powershift transmission incorporating torque converter, bevel box and a 4 speed powershift gearbox in one resiliently mounted unit. A combined steering column mounted switch incorporating directional control and 4 forward And 4 reverse powershift gears. Travel speed 15.5Mph (25Kph). |
| AXLES | Front and rear drive axles: JCB epicyclic hub reduction, drive/steer axles with JCB Max-Trac with torque proportioning differentials. Permanent 4 wheel drive. |
| BRAKES | Service brakes: servo assisted, hydraulically activated, self adjusting, oil immersed multi-disc type on front axle. Parking brake: hand operated disc brake on output of gearbox. |
| ELECTRICAL | 12 V negative earth, 130 Ah battery. 95 amp alternator. Reverse alarm. |
| INSTRUMENTS | Audio-visual warning system for: coolant temperature, engine oil pressure, air cleaner, battery charge, transmission oil temperature and pressure, water in fuel. Engine speed indicator, engine temperature, fuel gauge, clock and lateral inclinometer. All time display hour meter, visible from outside the cab. |
| STEERING | Hydrostatic power steering. Three steer mode options: front wheel steer, all wheel steer and crab steer operated from in the cab by a selection lever. |
| CAB/ CANOPY | Quiet, safe and comfortable cab/canopy conforms to ROPS ISO 3471 and FOPS ISO 3449. Available as safety frame or fully enclosed. (Right hand side and rear window standard on canopy.) |
| BOOM | 4 section boom with a max lift height of 56', hydraulic parallel lift, max lift capacity of 10,000 lbs. 'U' pressing design, made from high tensile steel. Low maintenance, hard wearing pads. |
| HYDRAULICS | Two stage gear pump, open center system. 29 gpm, 3,770 psi operating pressure. Single auxiliary hydraulic service on boom. |
| WARRANTY | 2 years or 2000 hours full coverage warranty (see the machine warranty certificate for details). |
| LIVELINK | 5 year subscription allows for enhanced machine security, improved service monitoring and modernized fleet. |





Features and Benefits

Standard Equipment and Features & Benefits related to this product are subject to change without notice

| | |
|---|--|
| Safety | A construction Loadall has hose burst check valves (HBCVs) to protect the rams from collapse in the event of a hose failure. |
| Versatility | A construction Loadall has three selectable steer modes. There's two wheel steer, which is ideal for travelling a high speed on the road; four-wheel steer for working in tight spaces; and crab steer for maneuvering close to walls and buildings. |
| Safety | For quick, easy and safe access, JCB Loadall operators maintain three points of contact when entering or exiting the machine. |
| Serviceability | Diesel and DEF tanks are filled from ground level and include built-in pre-filters in the filler necks to guard against dirt and contaminants. |
| Durability | JCB telehandlers undergo a stringent testing program that includes thousands of transmission cycles and prolonged high-stress loading of the chassis, boom and other key components. |
| JCB lift and place coupler with auxiliary hydraulic | Easy-to-use, single pin allows for simple attachment changes |
| Parallel lift/lower | Keeps forks level and load secure |
| Full opening hood | Easy service and excellent noise reduction |
| Sway control | Machine leveling on uneven terrain |
| Nylacast boom wear pads and waxoyl dry film lubricant | Excellent wear characteristics; dry lubricant does not collect abrasives and extends life of wear pads |
| Three steer modes | Selectable 2ws, 4ws and crab steer for excellent maneuverability |
| Cab - ROPS/FOPS certified; cab or canopy | Allows excellent visibility, comfort and protection for operator |
| Suspension seat and tilt steering wheel | Operator comfort for higher production and easy adaption |





Features and Benefits

Lift & place style joystick

Intuitive design puts operator comfort first

Axle mounted stabilizers

Stabilizers offer machine leveling on uneven terrain





Prepared For:
 DERRICK SPEIGHTS
 CITY OF HOLLISTER
 HOLLISTER CALIFORNIA

Dealer Information
 CENTRAL CALIFORNIA POWER JCB
 19487 BROKEN CT
 SHAFTER CA 93263
 phone:6615892870

Prepared By:
 Raul Portugal
 RAUL@GENSETS.COM
 mobile:
 Quote Date: 01/30/23
 Valid Until: 03/01/23
 Quotation Reference: 364615

Model: 510.56 F

Qty: 1

Equipment Description

510-56 USA 109HP (81KW) T4F
 SOLIDEAL 14-24SOLID FILL
 SERVO: SINGLE LEVER, 1 AUX,PLACING PATTERN 510 512 514
 CAB: STEEL LOWER DOOR PANEL 4F
 Fabric suspension seat with adjustable back with 2 inch
 seatbelt
 TOOL CARRIER QUICKHITCH - REQUIRED TO MOUNT CARRIAGE
 Operators Manual - English
 Sun shade
 Air Conditioning
 OPTIONAL: KEY PAD IMMOBILISER FOR FULL CAB BUILDS ONLY
 AVAILABLE DECEMBER 2021
 60 IN X 5 IN X 2 IN PALLET FORKS (2) FOR 2-1/4 IN FORK SHAFT
 OPTIONAL: PINTLE TOW HITCH
 FRONT AND REAR WORKLIGHTS
 ROTATING BEACON. MAGNETIC BASE.
 ENGINE SUMP DRAIN KIT
 FUEL TANK PROTECTION KIT TIER 4 FINALF
 72 inch Carriage, 2.25 inch Shaft, 12000 lb Capacity

| | |
|----------------------------------|-------------------|
| Equipment Total | 168,644.80 |
| CA Tire Tax / Recycle Fee | 10.00 |
| Total Customer Sale Price | 168,654.80 |

Notes: SOURCEWELL 20% DISCOUNT APPLIED

FRIEGHT FROM CCP SHAFTER CA TO CITY OF HOLLISTER CORP YARD CAN BE QUOTED 30 DAYS BEFORE PURCHASE/MOVE

Customer Acceptance: _____

Date _____

Dealer _____

Date _____

